

ELECTRIC STACKER

SE1016

SE1020

SE1225

SE1229

SE1235



SE1016 • SE1020 • SE1225 • SE1229 • SE1235

TECHNICAL DETAILS				SE1016	SE1020	SE1225	SE1229	SE1235
CAPACITY	Q	Nominal load	Kg	1000	1000	1200	1200	1200
CENTER OF GRAVITY	C	Distance	mm	600	600	600	600	600
DRIVING SYSTEM		Escort / Standing		Escort	Escort	Escort	Escort	Escort
DIMENSIONS								
ELEVATION	h3	Elevation	mm	1600	2000	2500	2900	3500
	h2	Normal free elevation	mm	1510	1910	-	-	80
LENGTH	l	Fork length	mm	1150	1150	1150	1150	1150
	nxS1	Fork width x thickness	mm	150x70	150 x 70	150x70	150x70	150x70
DIMENSIONS	L	Total length	mm	1825	1825	1825	1825	1825
	L2	Steer unit length	mm	675	675	675	675	675
	B	Width	mm	850	850	850	850	850
	h1	Minimum dimensions	mm	1970	2370	1780	1980	2250
	h4	Maximum dimensions	mm	1970	2370	2985	3385	3915
TURNING RADIUS	Wa		mm	1460	1460	1460	1460	1460
STOWAGE PASSAGE	Ast		mm	2075	2075	2075	2075	2075
PERFORMANCES								
SPEED		Translation with/without load	km/h	4,0/5,0	4,0/5,0	4,0/5,0	4,0/5,0	4,0/5,0
LIFTING		With/without load	m/s	0,09/0,12	0,09/0,12	0,07/0,10	0,07/0,10	0,07/0,10
DESCENT		With/without load	m/s	0,4/0,1	0,4/0,1	0,4/0,1	0,4/0,1	0,4/0,1
WEIGHT								
EMPTY WEIGHT		With battery	kg	390	410	490	505	540
AXLE LOADING		With load (driver/load)	kg	442/948	457/956	549/1141	563/1142	589/1151
		Without load (driver/load)	kg	287/103	302/111	362/128	376/129	402/138
FRAME								
WHEELS		Driver side/load	Nr	2+1 M/2	2+1M/2	2+1 M/2	2+1 M/2	2+1 M/2
TYRES		Driver side/load		P+G/P	P+G/P	P+G/P	P+G/P	P+G/P
		Drive wheel Ø	mm	240x60	240x60	250x76	250x76	250x76
		Stabilizer wheels Ø	mm	150x40	150x40	150x40	150x40	150x40
		Load side Ø	mm	82x70	82x70	82x70	82x70	82x70
OPERATING BRAKE				Electric	Electric	Electric	Electric	Electric
ELECTRICAL EQUIPMENT								
ELECTRIC MOTORS		Traction motor	kW	0,5	0,5	0,7	0,7	0,7
		Lifting motor	kW	2,2	2,2	2,2	2,2	2,2
SPEED CONTROL				Electric	Electric	Electric	Electric	Electric
BATTERY		Traction/Starter	type	S	S	S	S	S
		Voltage	V	24	24	24	24	24
		Capacity	Ah	70	70	92	92	92
		Endurance	h	3	3	3	3	3
		Weight	kg	36	36	44	44	44
CHARGER			V-A	24-13	24-13	24-20	24-20	24-20

G=Rubber, P=Polyurethane

